

Highlights

- Cuts energy cost by 90%
- 50,000 hour life expectancy o DC Voltage safe to handle
- UV stabilized housing
- Virtually no fire hazard on DCV side
- Virtually no breakage factor during handling and shipping
- Virtually no breakage factor after or during installation
- LED color matched to the housing
- Rigid but impact resistant housing
- Waterproof housing with pigtail connectors
- Simple and easy installation
- One year full replacement warrantee on all components
- Five year prorated warrantee on all components

Applications

Neon sign replacement,Decorate building edge highlighting,Sign edge,Car underbody lightbar, Restaurants,Home lighting source.

Description

Strip size: 24" L x 1 "W "d" Type 48 Ultra bright LEDs for a single color tube

48 Ultra bright red / 48 Ultra Bright green / 48 Ultra bright blue for RGB tube

120 degree viewing angle of even lighting Voltage options: 12 VDC/24VDC 240mA/120mA

Connector current rating: 6A

Part Number	Visible Color	Wavelength (nm)	No. LED	Lumen per segment
MCD-30STB24-48UR	Red	625	48	1.8
MCD-30STB24-48UY	Yellow	594	48	1.8
MCD-30STB24-48UG	Green	525	48	2.2
MCD-30STB24-48UB	Blue	470	48	1.0
MCD-30STB24-48UW	White	5000-6500K	48	2.0
MCD-30STB24-114RGB	RGB		114	